

HOT MELT GLUES	BASE	USAGE								TECHNICAL INFORMATION		
		PRIMERED ABS, PVC AND PP EDGEBANDING	VENEER EDGEBANDING	MELAMINE EDGEBANDING	LIPPINGS FROM MASSIVE WOOD	SOFTFORMING	CNC FOREM EDGEBANDING	MANUAL FOREM EDGEBANDING	HOLZHER CARTRIDGE SYSTEM	SOFTENING RANGE - KOFLEK HEATER	TEMPERATURE PROCESSING	PACK
JOWATHERM 280.30 TRANSPARENT	EVA UNFILLED	XX	XX	XX	XX	XX	XX	XX	-	90°C	180 - 200°C	GRANULATE 25 KG
JOWATHERM 280.40 TRANSPARENT	EVA UNFILLED	XX	XX	XX	XX	XX	X	-	-	100°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 282.20 NATURAL	EVA FILLED	X	X	XX	-	X	-	X	-	80°C	130 - 150°C	GRANULATE 25 KG
JOWATHERM 282.40 TRANSPARENT	EVA UNFILLED	XX	XX	XX	XX	XX	-	XX	-	85°C	130 - 150°C	GRANULATE 25 KG
JOWATHERM 284.00 NATURAL	EVA FILLED	X	XX	XX	-	X	-	-	-	90°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 288.50 NATURAL	EVA FILLED	XX	XX	XX	XX	XX	-	XX	-	95°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 288.91 WHITE	EVA FILLED	X	XX	XX	-	-	-	-	-	85°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 288.92 BROWN	EVA FILLED	X	XX	XX	-	-	-	-	-	85°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 288.93 BLACK	EVA FILLED	X	XX	XX	-	-	-	-	-	85°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 296.75 NATURAL	EVA FILLED	XX	XX	XX	-	X	-	-	-	85°C	190 - 210°C	GRANULATE 25 KG
JOWATHERM 286.30 TRANSPARENT	EVA UNFILLED	XX	XX	XX	XX	-	-	-	XX	90°C	180 - 200°C	CARTRIDGES 11,8 KG
JOWATHERM 286.60 NATURAL	EVA FILLED	XX	XX	XX	-	-	-	-	XX	80°C	180 - 200°C	CARTRIDGES 15,4 KG
JOWATHERM 286.61 WHITE	EVA FILLED	XX	XX	XX	-	-	-	-	XX	80°C	180 - 200°C	CARTRIDGES 15,4 KG
JOWATHERM 286.62 BROWN	EVA FILLED	XX	XX	XX	-	-	-	-	XX	80°C	180 - 200°C	CARTRIDGES 15,4 KG
JOWATHERM 286.63 BLACK	EVA FILLED	XX	XX	XX	-	-	-	-	XX	80°C	180 - 200°C	CARTRIDGES 15,4 KG

"XX" - VERY APPLICABLE, "X" - APPLICABLE, "-" - UNSUITABLE